Data Sheet

We make sure

FUJITSU COMPUTERS SIEMENS

SCENICVIEW XE19-2 B
19 Inch LCD Display

Issue October 2006

Pages 2

An attractive price doesn't mean that you have to compromise on style or performance. Sleek and space-saving, the SCENICVIEW XE19-2 B is the best choice LCD for those seeking to upgrade their bulky CRT with limited budget.

It offers best performance for the home office and multimedia such as photo editing, gaming and watching the latest DVDs.

Highlights

- Best performance to an affordable price
  - Office applications
  - Internet and multimedia are supported best
- Very easy and comfortable to use
  - Plug & Play
  - Auto-adjust
  - Easy-to-use OSD menu

Ergonomics

- Optimum flicker-free and distortion-free ergonomics
- Excellent colour purity
- Well balanced brightness uniformity
- Excellent high contrast (700:1)
- Space saving design

Technical highlights

- 19” (48cm) LCD Display
- Excellent contrast 700:1
- Brightness 250 cd/m^2
- Fast response time (typ.) 8ms

Reliability

- Low power consumption
- Power management according EPA
- Guaranteed quality and stability

Visible screen diagonal	19 inch (48 cm)
Graphics display (dependent on graphics processor)	
Pixels	1280 x 1024
Pixels*	1024 x 768
Pixels*	800 x 600
* expanded	
Highest resolution	1280 x 1024
Picture size	376.3 x 301 mm
Colours	16.2 million
Pixel Pitch	0.294 mm
Frequencies	
Horizontal	31 – 81 kHz
Vertical	56 - 75 Hz
Brightness (typical)	250 cd/m^2
Contrast (typical)	700:1
Viewing angle (typical)	
Horizontal	150°
Vertical	135°
Response time (typical)	8 ms
Plug and Play	VESA DDC2B
Setting options	
Brightness (Back light)	
Contrast, Volume control	
Picture position (horizontal and vertical)	
Color temperature and individual color setting	
Auto-adjust (direct access key)	
Activate factory settings	
Menu language	
OSD Language	
GB, D, F, I, E, PL, NL, RUS	
Base	
Tilt angle	-5° +20 °
Audio characteristics	
Audio signal input	RCA audio L/R
Audio output	1 W (L) + 1 W (R)

Electrical values	
Rated voltage	100 - 240 V
Frequency	50 - 60 Hz
Power draw	
Max.	< 50 W
Stand by	< 1 W
Protection class	1
Temperatures/dimensions/weight	
Ambient temperature (to IEC721)	
Working (recom.)	5°C to 35°C
Storage	-20°C to 60°C
Dimensions (H x W x D) (With Stand)	426 x 436 x 214 mm
Weight (Monitor only)	4.6 kg
Reliability	
MTBF (demonstrated)	70,000 h
Lifetime of LCD backlight (brightness > 50 % of original brightness)	50,000 h
Compliance with standards	
Product safety	EN60950, NEMKO
Ergonomics	GS mark ISO13406-2 (Pixel fault class II)
Radiation immunity and RFI suppression	CE certification according to EC Directive 89/336/EEC (EN55022/B, EN50082-1 EN61000-3-2/-3);TCO 99; FCC Class B part 15
Data cable (1.8 m)	1 x D-SUB (15-pin), 1 x Audio
Power cable (1.8 m)	For wall socket Euro-Schuko-Type CEE7
Integrated power adapter	
Plug type on Monitor	IEC-320-C13
Special features	Standardized mounting interface according VESA FPMPMI **(100 mm),** integrated audio
Order code	S26361-K1140-V180

All rights, including rights created by patent grant or registration of a utility model or design as well as rights of technical modifications are reserved. Delivery subject to availability. Designations may be trademarks, the use of which by third parties for their own purposes may violate the rights of the trademark owners.

Copyright © Fujitsu Siemens Computers,08/2005

Published by

Fujitsu Siemens Computers
http://www.fujitsu-siemens.com/

Company stamp